


Config Table

SKU#	Power Cord Length	Plug
AP53001	-	-
AP53001-20	6mm^2x5, 2M	-
AP53001-20P	6mm^2x5, 2M	IEC309 32A 3P6H IP44



IEC609 PLUG  
IP44 32A 5P6H

PUD Series: Meter By Bank  
 Input: 200-240V AC, 32A, 3Ph(3L+N+G)  
 Outlet: C13 [18], C19 [9].  
 CB/Bank: 16A/1P [3], 3xBank  
 Outlet Color: Black/White/Red  
 Chassics Color: Black

THIS DRAWING AND SPECIFICATIONS HEREIN ARE THE PROPERTY OF A-RACK AND SHALL NOT BE COPIED, REPRODUCED OR USED IN WHOLE OR IN PART, AS THE BASIS FOR THE MANUFACTURE OR SALE OF ITEMS WITHOUT WRITTEN PERMISSION FROM A-RACK. THIS DRAWING IS BASED UPON LATEST AVAILABLE INFORMATION AND IS SUBJECT TO CHANGE WITHOUT NOTICE.

Drawn by	Description	Drawing No.	
Approved by	Meter PDU, 200-240V AC, 32A 3Ph C13 [18], C19 [9]	AP53001	
	Version	Third Angle Projection	Unit: mm
	A1	A4	Sheet1 OF 1
Scale:	1:-		

Tolerance 1SD 2768-M  
 >3=6 ±0.1  
 >6=30 ±0.2  
 >30=120 ±0.3  
 >120=400 ±0.5  
 >400=1000 ±0.8