


Config Table

SKU#	Power Cord Length	Plug
AP83001	-	-
AP83001-20P	6mm^2x5, 2M	IEC309 32A 5P6H IP44



IEC609 PLUG
IP44 32A 5P6H

PUD Series: Meter & Switch by outlet
 Input: 200-240V AC, 32A, 3Ph (3L+N+G)
 Outlet: C13 [18], C19 [6].
 CB/Bank: 16A/1P [3], 3xBank
 Outlet Color: Black/White/Red
 Chassics Color: Black

THIS DRAWING AND SPECIFICATIONS HEREIN ARE THE PROPERTY OF A-RACK AND SHALL NOT BE COPIED, REPRODUCED OR USED IN WHOLE OR IN PART, AS THE BASIS FOR THE MANUFACTURE OR SALE OF ITEMS WITHOUT WRITTEN PERMISSION FROM A-RACK. THIS DRAWING IS BASED UPON LATEST AVAILABLE INFORMATION AND IS SUBJECT TO CHANGE WITHOUT NOTICE.

Drawn by	Description	Drawing No.	
Approved by	Meter & Switch by outlet PDU, 200-240V AC, 32A, 1Ph C13 [18], C19 [6]	AP83001	
		Version	Third Angle Projection
		A1	A4
Scale: 1:-		Unit: mm	Sheet1 OF 1

Tolerances/Tolerance $>0.5=3$ ± 0.1 $>3=6$ ± 0.1 $>6=30$ ± 0.2 $>30=120$ ± 0.3 $>120=400$ ± 0.5 $>400=1000$ ± 0.8 2768-M